



SISSONS PAINTS (THAILAND) LTD.

บริษัท ซีสชั่นส์เพ้นท์ส (ประเทศไทย) จำกัด

ได้รับการรับรองระบบคุณภาพมาตรฐาน ISO 9001 จาก SGS (Thailand) Limited.



91/2 หมู่ 3 ถนนสุวินทวงศ์ มีนบุรี กรุงเทพฯ 10510 โทร +66 (0) 2517 1146, 2918 6760 โทรสาร +66 (0) 2517 2137

## SISSONS ROAD LINE PAINT (Anti-Skid)

(Cold Plastic Road Marking Paint)

<b>PRODUCT DESCRIPTION</b>	A two component Road marking Paint. It is designed for traffic marking applications. Formulas contain coarse aggregates for excellent slip resistance properties. Due to special selection of resin, <b>Sissons Road Line Paint (Anti-Skid)</b> can be used in a long period of time because of its outstanding weathering resistance.	
<b>SPECIFIC PROPERTIES</b>	Excellent adhesion to asphalt and concrete surfaces Anti-Skid Properties High abrasion resistance Excellent Chemical resistance Excellent Weather resistance Slip resistance Easy to apply, not require many equipment and heater. Road marking materials. Wear simulator Turntable 4,000,000 around.(EN 13197)	
<b>PHYSICAL DATA</b>	<b>Solids</b>	98 % (by weight)
	<b>Dry Film Thickness</b>	3000 micron
	<b>Wet Film Thickness</b>	3000 micron
	<b>Flash Point</b>	> 11 °C
	<b>Theoretical Coverage</b>	2.0 kg/m <sup>2</sup> / mm
	<b>Colours</b>	Standard color (Red, Blue)
	<b>Glossiness</b>	Matt
	<b>Reflectivity</b>	Available glass beads for on-site mixing
	<b>Drying Time</b>	Surface Dry : 10-15 minutes Hard Dry : 1 hour (Max.)
	<b>Viscosity</b>	>140 KU @ 25 °C Stormer Viscometer
	<b>Specific Gravity</b>	1.60-2.0
<b>APPLICATION DATA</b>	<b>Application method</b>	Trowel, squeegee and roller
	<b>Temperature</b>	5 °C to 45 °C
	<b>Humidity Maximum</b>	85% R.H.
	<b>Mixing Ratio</b>	100 Base : 1 Hardener (by weight)
	<b>Thinner/ Cleaner</b>	Thinner No.36
<b>ADDITIONAL INFORMATION</b>	<b>Cleaning Solvent</b>	Thinner No.36
	<b>Packaging</b>	Two packs product Part A + Part B : 5.05 kg and 20.20 kg
<b>SAFETY PRECAUTIONS</b>	Ensure that there is adequate ventilation in the area where the product is being applied. Do not breath vapour or spray. Wear appropriate PPE. In case of touch skin, wash skin thoroughly with soap and water. In case of accidental eyes splashes, flush eyes with warm water and immediately obtain medical advice.	
<b>DISCLAIMER</b>	The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.	